PASO 750 DESMO

DUCATI

IL NOSTRO PASSA
HA UN GRANDE

ATO
E FUTURO



Castrol



DATI TECNICI

MOTORE

Tipo	bicilindrico 4-tempi ad "L"
Cilindrata	748 cm³
Alesaggio x corsa	88x61.5 mm
Potenza max	74 CV a 7900 giri/1'
Distribuzione	Desmodromica a camme in testa
Accensione	elettronica
Alimentazione	n. 1 carburatore WEBER doppio corpo 44 DCNF 107
Avviamento	elettrico
Trasmissione primaria	ad ingranaggi
Frizione	a dischi multipli a secco
Cambio	a 5 rapporti
Trasmissione secondaria	a catena

TELAIO

Lunghezza max.	2030 mm.
Larghezza max.	655 mm.
Interasse	1450 mm.
Peso a secco	195 Kg.
Capacità serbatoio	22 l.
Sospensione ant.	teleidraulica Ø 42 con "anti-dive"
Sospensione post.	forcellone oscillante in lega leggera con sospensione progressiva soft-damp
Freno anteriore	a doppio disco Ø 280
Freno posteriore	a disco Ø 270
Pneumatico ant.	130/60 ZR 16
Pneumatico post.	160/60 ZR 16

La Ducati Meccanica si riserva di modificare senza preavviso le caratteristiche sopra elencate.

SPECIFICATIONS

ENGINE

Type	L-Twin, four stroke
Displacement	748 cc
Bore x stroke	88x61.5 mm.
Max Power	74 HP at 7900 r.p.m.
Valve train	S.O.H.C., Desmodromic actuation
Ignition	electronic type
Carburetion	no. 1 WEBER two-barrel car 44 DCNF 107 type
Starter	electric
Primary drive	gears
Clutch	multi-plate, dry
Gearbox	five gear ratios
Final drive	chain

CHASSIS

Overall length	2030 mm.
Overall width	655 mm.
Wheelbase	1450 mm.
Dry wheight	195 Kg.
Fuel capacity	22 l.
Front suspension	Ø 42 tele-hydraulic type with anti-dive
Rear suspension	aluminium swing-arm with single shock absorber, gradually working, soft damp type
Front brake	double disc, Ø 280
Rear brake	disc, Ø 270
Front tire	130/60 ZR 16
Rear tire	160/60 ZR 16

The above specifications are subject to modification without notice.

DELTA '86

CAGIVA commerciale S.p.A.

Uffici Commerciali Amministrativi:
BOLOGNA - VIA A. CAVALIERI DUCATI n. 3
Tel. 051/405049 - Telex 510492 DUCMEC
Telefax 051/406580

CAGIVA DUCATI HUSQVARNA